

Amendments to the Specification

Please amend the specification, as follows:

Page 18, line 30 - page 19, line 2, replace the paragraph with the following amended paragraph:

The inner tube 4 is preferably moulded and vulcanized in a toroidal shape so as to ~~memorise~~ memorize this shape~~[[: in]]~~. In other words, when subjected to mechanical stresses ~~[[which]]~~ that deform it, ~~[[it]]~~ the inner tube 4 is able to produce elastic reactions designed to ensure that it reacquires the original undeformed shape. In particular, and more preferably, the inner tube is moulded and vulcanized with a toroidal shape having an internal volume not less than one third of the final volume of use.

Page 24, lines 9-20, replace the paragraph with the following amended paragraph:

On the periphery of this carcass there is arranged an annular overstructure, known as a belt structure 50, and a tread band 8. The belt structure ~~[[which]]~~ is normally composed of one or more strips of rubberized fabric ~~[[which]]~~ that are superimposed on each other so as to define a so-called "belt pack." ~~[[and a]]~~ The tread band 8 is made of elastomer material~~[[,]]~~ wound around the belt pack and moulded with a ~~raized~~ raised design for ~~[[the]]~~ rolling contact of the tyre on the road. Moreover, the carcass is provided, in axially-opposite lateral positions, with

FINNEGAN
HENDERSON
FARABOW
GARRETT &
DUNNER LLP

1300 I Street, NW
Washington, DC 20005
202.408.4000
Fax 202.408.4400
www.finnegan.com

two sidewalls 6 and 6' [[which]] that are made of elastomer material, ~~and each~~ Each sidewall
extends in the radial direction outwards from the external edge of the associated bead.

FINNEGAN
HENDERSON
FARABOW
GARRETT &
DUNNER LLP

1300 I Street, NW
Washington, DC 20005
202.408.4000
Fax 202.408.4400
www.finnegan.com